



Dividers

Part No.	BW(MHz)	Freq. (MHz)	I/L (dB)	Iso. (dB)	Phase Diff.	Amplitude Diff.	*Solder	*PKG	Application Note	Impedance		
BD09B	700-1000 Cellular, GSM900	750	0.49	20.2	0.5	0.02	with	SOIC8		50 Ohm		
		850	0.49	28.3	0.5						Deg	
		950	0.58	20.1	0.6							0.03
		750	0.5	20.6	0.2	0.01					without	
		850	0.52	27	0.2							Deg
		950	0.59	19.5	0.4							
BD0926	700-1000 Cellular, GSM900	750	0.55	22	0.2	0.01	without	SOT26		50 Ohm		
		850	0.57	31.4	0.2						Deg	0.01

רח' אודם 14, ת.ד. 7042 פ"ת ▪ טל: 03-9243352 ▪ פקס: 03-9243358

www.hypertech.co.il ▪ sales@hypertech.co.il



Part No.	BW(MHz)	Freq. (MHz)	I/L (dB)	Iso. (dB)	Phase Diff.	Amplitude Diff.	*Solder	*PKG	Application Note	Impedance	
		950	0.63	19	0.4	0.01					
BD19B	1700-2300 PCS, WCDMA	1700	0.35	20.4	0.2	Deg	0.03	dB	with	SOIC8	50 Ohm
		1900	0.38	24.4	0.3						
		2075	0.47	30.1	0.5						
		1700	0.38	20	1	Deg	0.06	dB	without		
		1900	0.43	24.1	1						
		2075	0.54	25.4	0.9						
BD1926	1700-2300 PCS, WCDMA	1700	0.51	20.1	1.4	Deg	0.04	dB	without	SOT26	50 Ohm
		1900	0.55	24.8	1.5						
		2075	0.63	21.6	1.5						
BD23B	1900-2500 PCS, WCDMA, WiBro, TD-SCDMA	1900	0.38	18.7	0.1	Deg	0.03	dB	with	SOIC8	50 Ohm
		2075	0.39	21.6	0.2						
		2350	0.46	28.5	0.5						
		1900	0.36	19.2	1.7	Deg	0.07	dB	without		
		2075	0.38	22.2	1.7						
		2350	0.49	25.8	1.7						

Part No.	BW(MHz)	Freq. (MHz)	I/L (dB)	Iso. (dB)	Phase Diff.	Amplitude Diff.	*Solder	*PKG	Application Note	Impedance	
BD2326	1900-2500 PCS, WCDMA, WiBro, TD-SCDMA	1900	0.58	23.3	0.7	Deg	0.03	dB	without	SOT26	50 Ohm
		2075	0.59	27.5	0.7		0.04				
		2350	0.69	19.5	0.6		0.06				
BD25B	1700-2500 PCS, PCS, USPCS, WCDMA, WiBro, TD-SCDMA	1800	0.38	20.8	0.2	Deg	0.07	dB	with	SOIC8	50 Ohm
		2075	0.42	25.7	0.4		0.09				
		2350	0.6	22.2	0.7		0.12				
		1800	0.41	21.1	1.5	Deg	0.08	dB	without		
		2075	0.49	26.3	1.7		0.11				
		2350	0.75	19	1.7		0.1				
BD2626	2400-2900 WCDMA, WiBro, LTE	2400	0.61	23.3	0.75	Deg	0.07	dB	without	SOT26	50 Ohm
		2500	0.59	25.1	0.75		0.07				
		2650	0.61	28.2	0.75		0.07				
		2800	0.66	25.8	0.75		0.09				
		2900	0.64	22	0.75		0.09				