



רח' אודם 14, ת.ד. 7042 פ"ת ▪ טל: 03-9243352 ▪ פקס: 03-9243358
www.hypertech.co.il ▪ sales@hypertech.co.il

היפר-טק
מערכות



TRIMBLE® TMX-2050™ DISPLAY

System

DC Power Supplied by TM-200, 27 Volts, 3.5 Amps
Processor 1 GHz quad core
Storage Primary embedded memory – 32 GB

Mechanical

Dimensions. 312 x 214 x 45 millimeters (12.3 x 8.4 x 1.8 inches)
(plus connectors)
Weight 2.5 kg (5.5 lb)
Mount. 4 M6 screws on 75 mm centers (3 inch)

Housing

Material Magnesium
Environmental Rating. IP55

Temperature

Operation 0 °C to 65 °C (32 °F to 149 °F)
Storage -40 °C to 85 °C (-40 °F to 185 °F)

LCD Display

Size (diagonal)..... 307 mm (12.1 inch)
Touchscreen Protective capacitive touch
Resolution 1280 x 800
Brightness (adjustable)..... 1000 candela/m²

Front Facing Camera

Type..... Low light level, color
Resolution 1.3 Megapixels

Connections

USB (1 side facing, 1 rear facing) USB 2.0
Ethernet (via TM-200)..... RJ45 Connector
CAN (sources 5VDC) RJ11 Connector
Port Expander (optional) 1 Port for CAN bus, I/O, and Serial
HDMI Output..... DVI Connector



www.trimble.com/agriculture

© 2015, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. TMX-2050 is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022503-1310

רח' אודם 14, ת.ד. 7042 פ"ת ▪ טל: 03-9243352 ▪ פקס: 03-9243358
www.hypertech.co.il ▪ sales@hypertech.co.il

