

KEY FEATURES

Proven GNSS-Aided Inertial technology from Trimble Applanix

Centimeter level mobile positioning accuracy

Industry leading continuous positioning performance in GNSS denied environments

Full position and orientation solution for direct georeferencing of imaging systems


EMBEDDED GNSS-INERTIAL SYSTEMS FOR CONTINUOUS MOBILE POSITIONING AND DIRECT GEOREFERENCING APPLICATIONS

The Trimble AP10 GNSS-Inertial System is an embedded GNSS-Inertial OEM board set plus Inertial Measurement Unit (IMU) in a compact form factor. It is designed to give system integrators the ability to harness the best in GNSS multi-frequency positioning technology, with the superior capabilities of inertial data for continuous mobile positioning in poor signal environments and for the orientation of imaging sensors.

The Trimble AP10 features a high-performance precision GNSS receiver and the industry leading Applanix IN-Fusion™ GNSS-Inertial integration technology running on a powerful, dedicated Inertial Engine (IE) board. This flexible and modular design ensures the ability to perform full high-powered GNSS-inertial processing without sacrificing performance, and an upgrade path to next generation GNSS boards as they become available.

PERFORMANCE YOU CAN TRUST

Whether it be guiding autonomous vehicles to winning finishes in the DARPA Urban challenge, navigating through tunnels, or georeferencing sensor data to centimeter level accuracy from high in the sky, Trimble GNSS with Applanix inertial technology has a proven track record of performance without compromise. With the Trimble AP products you know exactly what positioning performance you will get for your mobile application, period.



AP10 GNSS BOARD SET



ח' אודם 14, ת.ד. 7042 פ"ת ▪ 70: 03-9243352 ▪ פקס: 03-9243358

www.hypertech.co.il ▪ sales@hypertech.co.il



TRIMBLE AP10 GNSS-INERTIAL OEM SYSTEM

TECHNICAL SPECIFICATIONS

- Advanced Applanix IN-Fusion™ GNSS-Inertial integration technology
- Advanced Trimble Maxwell® 6 Custom GNSS survey technology (two chipsets)
- 220 Channels: (per chipset)
 - GPS: L1 C/A, L2C, L2E (Trimble method for tracking unencrypted) L5
 - GLONASS: L1 C/A and unencrypted P code, L2 C/A and unencrypted P code, L3 CDMA
 - BeiDou: B1, B2
 - GALILEO: L1 CBOC, E5A, E5B, E5AltBOC
 - QZSS: L1 C/A, L1C, L1 SAIF, L2C, L5, LEX
 - SBAS: L1 C/A (EGNOS/MSAS), L1 C/A and L5 (WAAS)
 - L-Band: OmniSTAR VBS, HP, XP and G2
- High precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- Support for optional Distance Measurement Indicator (DMI) input
- Support for optional GNSS Azimuth Measurement System (GAMSTM)
- Support for optional POSPac Mobile Mapping Suite post-processing software

INPUT/OUTPUT

LAN

Parameters	Time tag, status, position, attitude, velocity, track and speed, dynamics, performance metrics, raw IMU data (200 Hz), raw GNSS data (1 Hz)
Display Port	Low rate UDP protocol output (1 Hz)
Control Port	TCP/IP input for system commands
Primary Port	Real-time TCP/IP output (1 – 200 Hz)
Secondary Port	Buffered TCP/IP protocol output for data logging to external device (1 – 200 Hz)

Internal Logging (1 – 200 Hz)

Parameters	Time tag, status, position, attitude, velocity, track and speed, dynamics, performance metrics, raw IMU data (200 Hz), raw GNSS data (1Hz)
------------	--

RS232 Input

Parameter	AUX GPS Input (RTK, SBAS), CMR, CMR+, RTCM3, 18 & 19, RTCM1, RTCM9 RS232 NMEA Output (1 – 50 Hz)
Parameter	Position (\$xxGGA), Heading (\$xxHDT), Track and Speed (\$xxVTG), Statistics (\$xxGST), Attitude (\$PASHR), Time and Date (\$INZDA), Events (\$EVT1, \$EVT2)

Other I/O

1PPS	1 pulse-per-second Time Sync output, normally high, active low pulse (configurable)
Event Input (2)	Two time mark of external events. TTL pulses > 1 ms width, max rate 100 Hz.

PHYSICAL CHARACTERISTICS

Size	167 L x 100 W x 74 H
Weight	0.68 kg
Power	10 – 28 Volts DC, 20 Watts (max) Typical 1.1 W (L1 GPS + L1 GLONASS)
Connectors	I/O: Samtec QSH-060-01-L-D-DP-A-RT1
Power	Samtec TFM-105-12-S-D-LC
Antenna	MMCX receptacle

ENVIRONMENTAL CHARACTERISTICS

Temperature	15 deg C to 30 deg C (optimal accuracy performance) -40 deg C to +75 deg C (Operational) -55 deg C to +85 deg C (Storage)
-------------	---

PERFORMANCE SPECIFICATIONS (RMS ERROR)

Terrestrial Applications, (DMI required)

System Accuracy - Full GNSS Availability		
Real time Correction Source	Horizontal Accuracy (RMS)	Heading Accuracy (RMS)
Omnistar XP	0.25 m	0.30 deg
Omnistar VBS	1.00 m	0.35 deg

System Accuracy - 20 second outage		
Real time Correction Source	Horizontal Accuracy (RMS)	Heading Accuracy (RMS)
Omnistar XP	2.00 m	0.50 deg
Omnistar VBS	2.50 m	0.55 deg

System Accuracy - 60 second outage		
Real time Correction Source	Horizontal Accuracy (RMS)	Heading Accuracy (RMS)
Omnistar XP	9.0 m	0.90 deg
Omnistar VBS	10.0 m	1.00 deg

Specifications subject to change without notice.

© 2013, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. (07113)



TRIMBLE APPLANIX
85 Leek Crescent
Richmond Hill, Ontario
L4B 3B3, Canada
+1-289-695-6000 Phone
+1-905-709-6027 Fax



ח' אודם 14, ת.ד. 7042 פ"ת ■ טל: 03-9243352 ■ פקס: 03-9243358
www.hypertech.co.il ■ sales@hypertech.co.il