



Features



- EU, US supported
 - LoRaWAN 1.0.3
 - WiFi backhaul
 - Wall-type plug with multiple plug options
 - Power input: Wall plug type / USB type C port
 - 802.11 b/g/n, Client Mode
 - Cost-effective
 - Quick set-up
 - Compact design for mobile application
 - Built-in LoRa & WiFi antenna
 - ESP32-D0WD by Espressif Systems
 - FreeRTOS support with AWS Qualification
- Another optional firmware supports Packet Forwarder and Basic Station, which can TTN/ChirpStack LNS. Please contact us for more details.

The Minihub Pro is designed to enable connection to the AWS IoT Core. It is also a low-cost LoRaWAN compliant gateway utilizing a WiFi backhaul. It is a wall-plug type with interchangeable plug options. The gateway also includes a USB-C charging port that making it ideal for mobile applications or to enlarge signal coverage.

Specification

LoRa	
Chipset	Semtech SX1308 / SX1302
Channels	8 Channels
Receive Sensitivity	-140 dBm
Wi-Fi	
Mode	802.11 b/g/n, Client Mode
Tx Power	+20 dBm
Frequency Bands	2.4 GHz
WAN/LAN ports	Not Available
USB Port	USB Type-C (900mA)
Security	WPA/WPA2
Dimensions	90x80x40mm
Weight	200g
Operating Temperature	0-40°C
Type Approval	CE/FCC/IC/RCM/WPC/RoHS

Minihub Pro

Doc ver.: BQW_03_0032.003



SKU Details

SKU	Country	Channels	Frequency Band (MHz)	With AWS Qualified FreeRTOS
TBMH110868	Europe	8	EU868 (862~870)	
TBMH110915	USA	8	US915 (902~928)	
TBMH110868A	Europe	8	EU868 (862~870)	V
TBMH110915A	USA	8	US915 (902~928)	V

2021 © Browan Communications Inc., All Rights Reserved. This document is for planning purposes only, and is not intended to modify or supplement any specifications or warranties relating to products of Browan Communications. Browan may make changes to specifications and descriptions at any time, without notice.



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352

Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il