







PRODUCT DESCRIPTION

The XIS-1818 320kV[™] is a powerful X-Ray Inspection System (XIS) designed for screening cargo at airports, customs centers, transit hubs, and freight facilities. For higher throughput, its heavy roller bed conveyor is only 38 cm (15") above the floor, convenient for loading and unloading freight. Its 320kV generator provides the highest level of steel penetration and image resolution of any cargo system its size.

ABOUT ASTROPHYSICS

Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 40,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

TOMORROW'S TECHNOLOGY FOR TODAY'S SECURITY™

XIS-1818

GENERAL SPECIFICATIONS

Tunnel Size: (WxH)	181.1 cm x 180.7 cm 71.3″ x 71.1″
Dimensions: ² (LxWxH)	949.6 cm x 310.3 cm x 240.0 cm 373.8" x 122.2" x 94.5"
Net Weight: ²	12000 kg (26400 lbs)
Shipping Weight: ²	16135 kg (35570 lbs)
Conveyor Speed:	20 cm/s (39 ft or 12m/min) Forward or Reverse
Conveyor Height:	34.3 cm (13.5") from Floor
Conveyor Capacity:	3000 kg (6614 lbs) Evenly Distributed Load

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage:	320kV
Tube Current:	7.0 mA
Wire Resolution: ²	40 AWG Typical, 38 AWG Standard
Steel Penetration:1	80 mm Typical, 75 mm Standard
Cooling:	Sealed Di-Electric Oil Bath with Forced Air
Duty Cycle:	100%, No Warm-Up Procedure Required
Beam Direction:	Horizontally Sideward

Windows® OS

1920 x 1200

8 GB RAM

256 GB SSD

COMPUTER & VIDEO

Platform. Display Type: Display Resolution: Memory: Storage Capacity:

ENVIRONMENTAL

Operating Temperature: Storage Temperature: Humidity:

0°C - 40°C / 32°F - 104°F -20°C - 60°C / -4°F - 140°F Up To 95% Non-Condensing

220VAC +/- 10%, 50/60Hz, 100 Amp Min.

Uninterruptible Power Supply (UPS)

(Computer Operation)

Dual 24" Flat Panel Monitors

ELECTRICAL

System Power:

Power Conditioner:

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40) Typical Radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by the Federal Standard)

FEATURES

STANDARD

3 & 6 Color Imaging Black & White Imaging High Penetration Function Organic/Inorganic Imaging Picture Perfect Pseudo Color Reverse Monochrome

Atomic Z-Number Measurement Geometric Image Distortion Correction Material Discrimination Real-Time Image Manipulation

Auto Image Archiving Image Review Save Image (RGB)

Baggage Counter

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready Real-Time Self Diagnostics

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x

OPTIONAL

Barcode Scanning Density Alert Local Language Safe Passage® Computer Based Training Screener Assist Software Test Case Threat Image Protection (TIP) Software

Conveyor Capacity Load Increase External USB Ports Variable Conveyor Speed

Custom Paint Entry/Exit Roller Tables Environmental Kit

Radiation Meter

Footmat Operator Interlock



ISO 9001 & ISO 14001 CERTIFIED



²As tested on Astrophysics Inc. Test Piece.

¹Weight and dimensions of the system may vary depending on customization.

Contact sales@astrophysicsinc.com for the most updated brochures.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.



³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

ARG

14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352 Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

HYPER-TECH Systems