

XIS-5335S™



PRODUCT HIGHLIGHTS

Artificial Intelligence (AI)

Powerful 160kV Generator

Enhanced Imaging™

Windows® Operating System
with Intel® Core™ Processor

8-Color Imaging



PRODUCT DESCRIPTION

The XIS-5335S™ is a compact X-Ray Inspection System (XIS) that provides more power than any system with its tunnel size. Capable of fitting through standard doorways, the system's small footprint allows for easy relocation, while the powerful 160kV generator provides heightened detection. The #1 global manufacturer of critical infrastructure products, Astrophysics is the clear choice.

ABOUT ASTROPHYSICS

Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 40,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

XIS-5335S™

GENERAL SPECIFICATIONS

| | |
|-----------------------------------|------------------------------------------|
| Tunnel Size: | 53.3 cm x 35.8 cm (WxH) |
| Dimensions: ¹ | 133.1 cm x 76.4 cm x 122.5 cm (LxWxH) |
| Shipping Dimensions: ¹ | 144.8 cm x 86.4 cm x 160.0 cm (LxWxH) |
| Net Weight: ¹ | 333 kg (734 lbs) |
| Shipping Weight: ¹ | 365 kg (804 lbs) |
| Conveyor Speed: | 23 cm/s (45 ft/min) Forward or Reverse |
| Conveyor Height: | 72.9 cm (28.7") from Floor |
| Conveyor Capacity: | 165 kg (364 lbs) Evenly Distributed Load |

X-RAY GENERATOR & IMAGE PERFORMANCE

| | |
|---------------------------------|---------------------------------------------|
| Voltage: | 160kV, Operating at 150kV |
| Tube Current: | 0.7 mA |
| Wire Resolution: ² | 40 AWG Typical, 38 AWG Standard |
| Steel Penetration: ² | 39 mm Typical, 37 mm Standard |
| Cooling: | Sealed Di-Electric Oil Bath with Forced Air |
| Duty Cycle: | 100%, No Warm-Up Procedure Required |
| Beam Direction: | Diagonally Upward |

COMPUTER & VIDEO

| | |
|---------------------|--------------------------|
| Platform: | Windows® 10 OS |
| Memory: | 8 GB RAM |
| Storage Capacity: | 256 GB SSD |
| Display Type: | 21.5" Flat Panel Monitor |
| Display Resolution: | 1920 x 1080 |

ENVIRONMENTAL

| | |
|------------------------|-------------------------------|
| Operating Temperature: | 0°C to 40°C / 32°F to 104°F |
| Storage Temperature: | -20°C to 60°C / -4°F to 140°F |
| Humidity: | Up To 95% Non-Condensing |

ELECTRICAL

| | |
|--------------------|---------------------------------------------------------------------------|
| System Power: | 110 VAC +/- 10% 50/60Hz, 15 Amp Max 220VAC +/- 10% 50/60Hz, 10 Amp Max |
| Power Conditioner: | Automatic Voltage Regulator (AVR), 600VA |

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)
Typical radiation leakage is less than 0.1 mR/hr
(Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

ISO 9001 & ISO 14001 CERTIFIED



¹Weight and dimensions of the system may vary depending on customization.

²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

^{4/5}Conveyor length will vary depending on system's dimensions.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.
Contact sales@astrophysicsinc.com for the most updated brochures.

FEATURES

STANDARD

- 3 & 6 Color Imaging
- Black & White Imaging
- Enhanced Imaging™
- High Penetration Function
- Organic/Inorganic Imaging
- Pseudo Color
- Reverse Monochrome
- Atomic Z-Number Measurement
- Geometric Image Distortion Correction
- Material Discrimination
- Real-Time Image Manipulation
- Auto Image Archiving
- Image Review
- Save Image (RGB)
- Baggage Counter
- Image Annotation
- JPEG Conversion
- Print Image Capable
- Multi-Tier Accessibility
- Network Ready
- Real-Time Self Diagnostics
- 9 Quadrant Zoom
- Continuous Scanning
- Continuous Zoom Up to 64x
- Vertical Zoom Panning

OPTIONAL

- Artificial Intelligence (AI)
- Barcode Scanning
- Density Alert
- Local Language
- Safe Passage® Computer Based Training
- Screeener Assist Software
- Test Case
- Threat Image Projection (TIP) Software
- External USB Ports
- Conveyor Capacity Load Increase
- Variable Conveyor Speed
- 24" Flat Panel Monitor
- Custom Paint
- Environmental Kit
- Entry/Exit Roller Tables
- Footmat Operator Interlock
- Roller Bed
- Short Conveyor⁴
- Long Conveyor⁵
- Mobility Kit
- Radiation Meter
- Remote Workstation Configuration
- Internal/External UPS
- 8-Color Imaging

XIS-5335S™ WITH MOBILITY KIT

| | |
|----------------------------------------|---------------------------------------|
| Dimensions¹ | 133.1 cm x 76.4 cm x 131.5 cm (LxWxH) |
| Shipping Dimensions¹ | 144.8 cm x 86.4 cm x 168.9 cm (LxWxH) |
| Net Weight¹ | 363 kg (800 lbs) |

